

28U Dual Bay Outdoor Enclosure, Aluminum, 150W Heat Exchanger, IP55



Description

This 28U dual bay outdoor enclosure is designed to protect expensive outdoor equipment or supply power supply in harsh environments, with waterproof and dustproof features. Dual Bay design to provide the adequate space for equipment. Cooling of active equipment is achieved by 150W heat exchanger, along with the vented front door and side door/panel. Various monitoring sensors such as smoke, and access control are installed in the enclosure, allowing personnel to monitor the operation status of the cabinets in real-time.

- Front door and side door access, convenient for installation and maintenance.
- Equipped with door mounted 150W heat exchanger, along with the vented front door and side door/panel, for thermal control

General Specification

Material	Aluminum, 3.0 mm Thickness
Finish	Powder Coating
Color	RAL7035 Light Grey
External Dimension	H403xW1400x540 mm, without Plinth and Top Cover
Protection Level	IP55
Installation	Pad Mount
Access	Front Door and Side Door
Maximum Door Opening	120°
Rack Mount	19"
Locking Mechanism	3 Point Locking
Cable Access	3pcs of PG29 Cable Entries at the Bottom
Other Included Parts	1pc of Ground Bar, 4pcs of L-Rails, 1*16 Pin Terminal Block (UK2.5N)

Cooling System

1 X Heat Exchanger, 150W, -48VDC

LED Lighting

5W Led Light 48VDC

28U Dual Bay Outdoor Enclosure, Aluminum, 150W Heat Exchanger, IP55



Sensors

Smoker Sensor	1*DC 48V Smoker Sensor
Door Sensor	2*Door Limit Sensor

Environmental Parameter

Operating Temperature	-40°C to +55°C
Storage Temperature	-40°C to +70°C
Humidity	5%-95%

Ordering Information

Part No.	Description
73021000	28U Dual Bay Outdoor Enclosure, Aluminum, 150W Heat Exchanger, IP55

Note: we accept customization for outdoor enclosures, kindly send email to support@nbspringsystem.com for more details.